

Performance Table (AQ-22LAW)

Nozzle Colour & Size		Pressure		Coverage Diameter		Flow Rate		MSH* (cm)
mm	inch	kg/cm ²	PSI	mtr	ft	LPH	GPM	
2.0 White	5/64" White	1.0	14	13.5	44.3	167	0.7	60-80
		1.5	21	16.0	52.5	205	0.9	
		2.0	28	17.0	55.8	237	1.0	
		2.5	36	17.0	55.8	265	1.2	
		3.0	43	17.5	57.4	290	1.3	
2.2 Brown	11/128" Brown	1.0	14	13.5	44.3	200	0.9	65-85
		1.5	21	16.5	54.1	245	1.1	
		2.0	28	17.0	55.8	283	1.2	
		2.5	36	17.5	57.4	316	1.4	
		3.0	43	18.0	59.1	346	1.5	
2.5 Purple	13/128" Purple	1.0	14	14.5	47.6	240	1.1	70-90
		1.5	21	16.0	52.5	294	1.3	
		2.0	28	18.0	59.1	340	1.5	
		2.5	36	18.5	60.7	380	1.7	
		3.0	43	19.0	62.3	416	1.8	

- Performance is based on ideal conditions of temperature, wind velocity and humidity.
- Tested at 50cm (1.5 ft.) height above the ground.
- *MSH-Max. stream height (from nozzle)

